




Screw-Screwless Connectors

900 Q RZ/ 5

Order Info

reference number (ref. no.)	114205
PU	500
EAN	4028012104482



Type

Type	Terminal Block
connection type	screw plug-in
number of poles	5 pole
colour	white

Electrical Data

rated voltage	450 V
rated current	17.5 A

Connection Data

cross-section rating	1.5 / 2.5 mm ²
cross-section rating internal	1.5 mm ²
cross-section rating external	2.5 mm ²
cross-section rating (UL)	20-16 AWG
clamping range external	0.5 - 1.5 mm ²
type of conductor internal	solid
type of conductor external	fine stranded, stranded, solid
stripping length internal	7.0 - 7.5 mm
stripping length external	8.0 - 8.5 mm
fixing	short catch pin
clamping units per pole	4
contact screw assembly	0.8 x 4.0 / \curvearrowright 0.5 Nm
wall thickness	0.5 - 1.4 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
ammonia resistance	yes

Materials

insulator material	PA
contact material	brass

flammability rating acc. to UL 94	V-2
-----------------------------------	-----

Approvals

acc. to EN 60998	yes
------------------	-----

acc. to UL	yes
------------	-----

acc. to CSA	yes
-------------	-----

acc. to CE	yes
------------	-----

acc. to UKCA	yes
--------------	-----

Accessories

ZEL 110	196420
---------	--------
