



Fused Terminal Blocks

1003 SI/ 1 GW



Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 11619 |
| PU | 100 |
| EAN | 4028012143979 |

Type

| | |
|-----------------|---|
| Type | screw terminal block with fuse holder 6,3x25/6,3x32 |
| connection type | screw |
| number of poles | 1 pole |
| colour | natural |

Electrical Data

| | |
|---------------|-------|
| rated voltage | 500 V |
| rated current | 16 A |

Connection Data

| | |
|----------------------------|---------------------------------------|
| rated connecting capacity | 4.0 mm ² |
| cross-sectional area (UL) | 22-10 AWG |
| clamping range | 0.5-12.0 mm ² |
| type of conductor | fine stranded, stranded, solid |
| type of conductor internal | fine stranded, stranded, solid |
| type of conductor external | fine stranded, stranded, solid |
| stripping length | 7.5-8.0 mm |
| clamping units per pole | 1 |
| contact screw assembly | 0.8 x 4.0 / \curvearrowright 0.8 Nm |
| socket diameter | 4.00 mm |

Ambient Conditions

| | |
|---|--------|
| T _{max} ambient air (at rated current) | 85 °C |
| T _{min} ambient air (operation) | -40 °C |
| T _{max} component (operation) | 105 °C |

Materials

| | |
|-----------------------------------|-------|
| insulator material | PA GW |
| contact material | brass |
| flammability rating acc. to UL 94 | V-2 |

Approvals

acc. to EN 60127

acc. to UL

acc. to CSA

Accessories

ZEL 110

196420
