



Connectors System AC 164  
Plug and Socket Connectors Flat Version

## AC 164 STF/ 3 SW



### Order Info

reference number (ref. no.)	146463
PU	200
EAN	4028012117260

### Type

Type	plug
Type1	plug
connection type	screw
number of poles	3 pole
coding	1 (mains) black
colour	black
protection against incorrect plugging	yes
PE-function	yes
latch	yes
maintenance-free	no

### Electrical Data

rated voltage	250 V
rated voltage (UL)	600 V
rated current	16 A
rated current (UL)	16 A
rated impulse voltage	4.0 kV

### Connection Data

cross-sectional area (UL)	16 AWG
clamping range	0.5-2.5 mm <sup>2</sup>
sheathing cable diameter	5.4-10.0 mm
type of conductor	fine stranded, stranded, solid
stripping length	7.0 mm
dismantling length	22.0 mm
dismantling length PE	29.0 mm
clamping units per pole	1
contact screw assembly	PZ 1 / ⌀ 0.5 Nm
pole marking	L1 ⊕ N
strain relief assembly	PZ 1 / ⌀ 0.5 Nm

## Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	70 °C
IP Code acc. to EN 60529	IP20
IP Code when plugged	IP40

## Materials

insulator material	PA
contact material	brass
flammability rating acc. to UL 94	V-2
halogen-free	yes

## Approvals

acc. to EN 61535
acc. to UL

## Accessories

AC 164 VT 3/3 SW	149763
------------------	--------