



## Screw Terminal Blocks

# 230/ 2 BD N L

### Order Info

reference number (ref. no.)	19211
PU	3,000
EAN	4028012133338

### Type

Type	terminal block
connection type	screw
number of poles	2 pole
colour	natural

### Electrical Data

rated voltage	450 V
rated current	24 A

### Connection Data

rated connecting capacity	2.5 mm <sup>2</sup>
cross-sectional area (UL)	22-12 AWG
clamping range	0.5-7.0 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
stripping length	5.0-5.5 mm
fixing	Screw
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\curvearrowright$ 0.5 Nm
mounting hole diameter	2.8 mm
socket diameter	3.10 mm
pole marking	N L
pin spacing	8.0 mm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C
T <sub>max</sub> component (operation)	105 °C

### Materials

insulator material	PA
contact material	brass

flammability rating acc. to UL 94

V-2

---

## Approvals

---

acc. to EN 60998

---

acc. to UL

---

acc. to CSA

---

## Accessories

---

230 BZ/ 2

191202

---

ZEL 110

196420

---