



## Fused Terminal Blocks

# 503 SI/ 3 GW

### Order Info

reference number (ref. no.)	19951
PU	200
EAN	4028012143825



### Type

Type	screw terminal block with fuse holder 5x20
connection type	screw
number of poles	3 pole
colour	natural

### Electrical Data

rated voltage	400 V
rated current	10 A

### Connection Data

rated connecting capacity	2.5 mm <sup>2</sup>
cross-sectional area (UL)	22-12 AWG
clamping range	0.5-9.0 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
type of conductor internal	fine stranded, stranded, solid
type of conductor external	fine stranded, stranded, solid
stripping length	7.0-7.5 mm
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\curvearrowright$ 0.5 Nm
mounting hole diameter	3.1 mm
socket diameter	3.50 mm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C
T <sub>max</sub> component (operation)	105 °C

### Materials

insulator material	PA GW
contact material	brass
flammability rating acc. to UL 94	V-2

## Approvals

---

acc. to EN 60127

---

acc. to UL

---

acc. to CSA

---

## Accessories

---

ZEL 110	196420
---------	--------

---

ABK 503/ 3 GW	193813
---------------	--------

---