



Fused Terminal Blocks

503 SI/ 4 DS GW



Order Info

reference number (ref. no.)	19956
PU	200
EAN	4028012143863

Type

Type	screw terminal block with fuse holder 5x20
connection type	screw
number of poles	4 pole
colour	natural
wire protection	yes

Electrical Data

rated voltage	400 V
rated current	10 A

Connection Data

rated connecting capacity	2.5 mm ²
cross-sectional area (UL)	22-12 AWG
clamping range	0.5-5.5 mm ²
type of conductor	fine stranded, stranded, solid
type of conductor internal	fine stranded, stranded, solid
type of conductor external	fine stranded, stranded, solid
stripping length	7.0-7.5 mm
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / \curvearrowright 0.5 Nm
mounting hole diameter	3.1 mm
socket diameter	2.75 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{min} ambient air (operation)	-40 °C
T _{max} component (operation)	105 °C

Materials

insulator material	PA GW
contact material	brass

flammability rating acc. to UL 94

V-2

Approvals

acc. to EN 60127

acc. to UL

acc. to CSA

Accessories

ZEL 110

196420

ABK 503/ 4 GW

193814