




## Fused Terminal Blocks

# 503 SI/ 5 MDS GW



### Order Info

reference number (ref. no.)	25066
PU	100

### Type

Type	screw terminal block with fuse holder 5x20
connection type	screw
number of poles	5 pole
colour	natural
centre stop	yes

### Electrical Data

rated voltage	400 V
rated current	10 A

### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 5.5 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
type of conductor internal	stranded, solid
type of conductor external	stranded, solid
stripping length	7.0 - 7.5 mm
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\curvearrowright$ 0.5 Nm
socket diameter	2.75 mm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C

### Materials

insulator material	PA GW
contact material	brass
flammability rating acc. to UL 94	V-2

## Approvals

acc. to EN 60127	yes
acc. to UL	yes
acc. to CE	yes
acc. to UKCA	yes

## Accessories

ZEL 110	196420
ABK 503/ 5 GW	193815