



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 179 kompakt

AC 179 SVH 4/ 4 SL L LWD



Order Info

reference number (ref. no.) 26762

PU 50

Type

Type	distributor longitudinally watertight
connection type	screw
number of poles	4 pole
colour	green black
centre stop	yes
strain relief	yes

Electrical Data

rated voltage	450 V
rated current	17.5 A

Connection Data

clamping range	0.5-1.5 mm ²
sheathing cable diameter	7.0-13.5 mm
type of conductor	fine stranded, stranded, solid
stripping length	6.0 mm
dismantling length	25.0 mm
clamping units per pole	1
grommet assembly	⌚ 2.0 Nm
contact screw assembly	M3 - max. ⌚ 0.8 Nm
pole marking	1-2-3-4
strain relief assembly	⌚ 2.5 Nm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{max} component (operation)	125 °C
T _{min} component (operation)	-40 °C
IP Code acc. to EN 60529	IP68/IP69

Materials

insulator material	PA
--------------------	----

contact material	brass
flammability rating acc. to UL 94	V-0

Accessories

AC 179 RVK/ 4 M20	749564
AC 173 BC SW	26280
DR 16 1x14,0	729031
DR 16 1x4,0	729033
DR 16 1x6,5	729034
DR 16 2x4,0	729035
DR 16 2x5,5	729036
DR 16 3x4,0	729037
DR 16 4x3,5	729038
DR 16 5x3,5	729009
DR 16 RH	729011
DR 16 GS	729032