



Screwless Connectors Block Connectors

930-00/ 2

terminal block without release keys, 2 pole, printing: L1 L2 L3 N PE,
voltage rating: 450 V, current rating: 24.0 A, cross-section
rating: 2.5 mm²



Order Info

| | |
|------------------------------------|---------------|
| reference number (ref. no.) | 112002 |
| PU | 1,000 |
| EAN | 4028012100255 |

Type

| | |
|--------------------------------|-------------------------------------|
| type | terminal block without release keys |
| number of poles | 2 pole |
| clamping units per pole | 2 |
| colour | white |
| cross-section rating | 2.5 mm ² |
| connection type | screwless |
| printing | L1 L2 L3 N PE |

Technical Data

| | |
|---|---------------------|
| voltage rating | 450 V |
| current rating | 24.0 A |
| insulating material | PA 6.6 |
| contact material | brass |
| flammability rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| stripping length | 8.0-9.0 mm |
| internal core cross-section max. | 2.5 mm ² |
| external core cross-section min. | 0.5 mm ² |
| external core cross-section max. | 2.5 mm ² |
| internal core cross-section min. | 0.5 mm ² |
| Type of Conductor Solid External | yes |
| Type of Conductor Solid Internal | yes |

Approvals

| | |
|-------------------------|------------------------------|
| acc. to EN 60998 | Download PDF |
| acc. to UL | Download PDF |

acc. to CSA

[Download PDF](#)
