




Screw-Screwless Connectors

900-07 RZ/ 6

Order Info

reference number (ref. no.)	114806
PU	500
EAN	4028012104918



Type

Type	Terminal Block
connection type	screw plug-in
number of poles	6 pole
colour	white

Electrical Data

rated voltage	450 V
rated current	17.5 A

Connection Data

cross-section rating	2.5 mm ²
cross-section rating internal	1.5 mm ²
cross-section rating external	2.5 mm ²
clamping range	- 12.0 mm ²
clamping range external	0.5 - 2.5 mm ²
type of conductor internal	solid
type of conductor external	fine stranded, stranded, solid
stripping length internal	7.0 - 7.5 mm
stripping length external	8.0 - 8.5 mm
fixing	short catch pin
clamping units per pole	2
contact screw assembly	0.8 x 4.0 / $\cup$ 0.5 Nm
socket diameter	4.00 mm
wall thickness	0.5 - 1.4 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
---	-------

Materials

insulator material	PA
--------------------	----

contact material	spring steel, steel
flammability rating acc. to UL 94	V-2

Approvals

acc. to EN 60998	yes
acc. to UL	yes
acc. to CSA	yes

Accessories

ZEL 110	196420
----------------	--------