



## Screw-Screwless Connectors

### 900 ED FR

#### Order Info

|                             |               |
|-----------------------------|---------------|
| reference number (ref. no.) | 115113        |
| PU                          | 5,000         |
| EAN                         | 4028012105007 |



#### Type

|                 |                |
|-----------------|----------------|
| Type            | Terminal Block |
| connection type | screw plug-in  |
| number of poles | 3 pole         |
| colour          | natural        |

#### Electrical Data

|               |        |
|---------------|--------|
| rated voltage | 450 V  |
| rated current | 13.5 A |

#### Connection Data

|                               |                                |
|-------------------------------|--------------------------------|
| cross-section rating          | 1.0 / 2.5 mm <sup>2</sup>      |
| cross-section rating internal | 1.0 mm <sup>2</sup>            |
| cross-section rating external | 2.5 mm <sup>2</sup>            |
| clamping range external       | 0.5 - 1.0 mm <sup>2</sup>      |
| type of conductor internal    | solid                          |
| type of conductor external    | fine stranded, stranded, solid |
| stripping length internal     | 7.0 - 7.5 mm                   |
| stripping length external     | 8.0 - 8.5 mm                   |
| fixing                        | short catch pin                |
| clamping units per pole       | 2                              |
| contact screw assembly        | 0.8 x 4.0 / $\cup$ 0.5 Nm      |

#### Ambient Conditions

|                                                 |       |
|-------------------------------------------------|-------|
| T <sub>max</sub> ambient air (at rated current) | 85 °C |
|-------------------------------------------------|-------|

#### Materials

|                                   |       |
|-----------------------------------|-------|
| insulator material                | PA    |
| contact material                  | brass |
| flammability rating acc. to UL 94 | V-2   |

Approvals

Accessories

---

**ZEL 110**

196420

---