



Screw Terminal Blocks

230/ 2 DS

Order Info

reference number (ref. no.)	121302
PU	3,000
EAN	4028012105229



Type

Type	Terminal Block
connection type	screw
number of poles	2 pole
colour	naturalal
wire protection	yes

Electrical Data

rated voltage	450 V
rated current	24 A

Connection Data

cross-section rating	2.5 mm ²
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 4.0 mm ²
type of conductor	fine stranded, stranded, solid
stripping length	5.0 - 5.5 mm
fixing	Screw
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / \cup 0.5 Nm
mounting hole diameter	2.8 mm
socket diameter	2.40 mm
pin spacing	8.0 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{min} ambient air (operation)	-40 °C

Materials

insulator material	PA
contact material	brass

flammability rating acc. to UL 94	V-2
--	-----

Approvals

acc. to EN 60998	yes
-------------------------	-----

acc. to UL	yes
-------------------	-----

acc. to CSA	yes
--------------------	-----

Accessories

230 BZ/ 2	191202
------------------	--------

ZEL 110	196420
----------------	--------
