



Screw Terminal Blocks

1000/ 2 DS

terminal block, 2 pole, insulating material: PA 6, cross-section rating: 6.0 mm², pin spacing: 12.0 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 41 A



Order Info

reference number (ref. no.)	125302
PU	1,000
EAN	4028012106172

Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	6.0 mm ²
wire protector (DS)	yes

Technical Data

voltage rating	500 V
current rating	41 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	6.0 mm ²
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
Assembly Contact Screw	0.8x4.0 / ⚓ 0.8 Nm
pin spacing	12.0 mm
fixing	screw

Approvals

acc. to EN 60998

[Download PDF](#)

acc. to UL [Download PDF](#)

acc. to CSA [Download PDF](#)

Accessories

1000 BZ/ 2 191402

ABK 406/ 2 193302

ZEL 110 196420
