




Connectors System AC 164 Panel Mounting

AC 164 EBU/ 2 WS

socket, 2 pole, white, coding: 1 (mains), voltage rating: 250 V, current rating: 16.0 A, cross-section rating: 1.5 mm², wall thickness min.: 0.5 mm, wall thickness max.: 1.2 mm



Order Info

reference number (ref. no.)	148652
PU	100
EAN	4028012123902

Type

type	socket
number of poles	2 pole
clamping units per pole	1
colour	white
coding	1 (mains)
cross-section rating	1.5 mm ²
connection type	screw
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	250 V
current rating	16.0 A
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	1.5 mm ²
impulse voltage rating	4.0 kV
flammability rating	V-2
max. Ambient Temperature Operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0 mm

Assembly Contact Screw	PZ 1 / \cup 0.5 Nm
-------------------------------	----------------------

wall thickness min.	0.5 mm
----------------------------	--------

wall thickness max.	1.2 mm
----------------------------	--------

Approvals

acc. to EN 61535	Download PDF
-------------------------	------------------------------

acc. to UL	Download PDF
-------------------	------------------------------