



Connectors 160/163

163 ST/ 3 DS

plug, 3 pole, wire protector (DS): yes, black, voltage rating: 400 V, cross-section rating: 2.5 mm²



Order Info

reference number (ref. no.)	151183
PU	200
EAN	4028012100088

Type

type	plug
number of poles	3 pole
clamping units per pole	1
colour	black
cross-section rating	2.5 mm ²
connection type	screw
PE function	yes
protection against incorrect plugging	yes
wire protector (DS)	yes

Technical Data

voltage rating	400 V
current rating	16.0 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	2.5 mm ²
impulse voltage rating	4.0 kV
flammability rating	V-2
max. Ambient Temperature Operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	6.5-7.0 mm
Assembly Contact Screw	0.6x3.5 / ⚙ 0.5 Nm

Approvals

acc. to EN 61984	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

163/ 3 ABK	192303
163/ 3 ZEL	192203