



Circular Connectors IP68  
Circular Connectors AC 169 kompakt

AC 169 REBU/5 M20



Order Info

reference number (ref. no.)	18907
PU	200
EAN	4028012133130

Type

Type	panel mount socket
connection type	screw
number of poles	5 pole
colour	black
protection against incorrect plugging	yes
PE-function	yes

Electrical Data

rated voltage	500 V
rated current	17.5 A
rated impulse voltage	4.0 kV
protection class acc. to EN 61140	SK II

Connection Data

cross-section rating	1.5 mm <sup>2</sup>
clamping range	0.25 - 1.5 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
stripping length	6.0 mm
clamping units per pole	1
lock nut assembly	1.5 Nm
contact screw assembly	M2 - max. $\cup$ 0.2 Nm
housing hole	M20
pole marking	1-2-3-4-E
wall thickness	1.0 - 9.0 mm

Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	60 °C
T <sub>max</sub> component (operation)	125 °C
T <sub>min</sub> component (operation)	-40 °C

<b>IP Code acc. to EN 60529</b>	IP66/IP68
---------------------------------	-----------

## Materials

<b>insulator material</b>	PA 6.6
---------------------------	--------

<b>contact material</b>	brass
-------------------------	-------

<b>flammability rating acc. to UL 94</b>	V-0
--	-----

## Approvals

<b>acc. to EN 61984</b>	yes
-------------------------	-----

## Accessories

<b>AC 169 RVKB M20</b>	729184
------------------------	--------