



## Fused Terminal Blocks

### 503 SI/ 3 GW

screwklemme, 3 pole, cross-section rating: 2.5 mm<sup>2</sup>, voltage rating: 400 V, current rating: 10.0 A



#### Order Info

reference number (ref. no.)	19951
PU	200
EAN	4028012143825

#### Type

type	screwklemme
number of poles	3 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
connection type	screw

#### Technical Data

voltage rating	400 V
current rating	10.0 A
insulating material	PA 6.6-GW
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	6.0 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 0.5 Nm
mounting hole diameter	3.1 mm
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

<b>Type of Conductor Flexible Internal</b>	yes
--	-----

## Approvals

<b>acc. to EN 60127</b>	<a href="#">Download PDF</a>
-------------------------	------------------------------

<b>acc. to UL</b>	<a href="#">Download PDF</a>
-------------------	------------------------------

<b>acc. to CSA</b>	<a href="#">Download PDF</a>
--------------------	------------------------------

## Accessories

<b>ZEL 110</b>	196420
----------------	--------

<b>ABK 503/ 3 GW</b>	193813
----------------------	--------