



## Fused Terminal Blocks

### 503 SI/ 4 E DS GW

screwklemme mit PE terminal am Blech, 4 pole, wire protector (DS): yes, cross-section rating: 2.5 mm<sup>2</sup>, voltage rating: 400 V, current rating: 10.0 A



### Order Info

reference number (ref. no.)	19959
PU	200
EAN	4028012143917

### Type

type	screwklemme mit PE terminal am Blech
number of poles	4 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
connection type	screw
wire protector (DS)	yes

### Technical Data

voltage rating	400 V
current rating	10.0 A
insulating material	PA 6.6-GW
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / ⚓ 0.5 Nm
mounting hole diameter	3.1 mm
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes

<b>Type of Conductor Stranded Internal</b>	yes
--	-----

<b>Type of Conductor Flexible Internal</b>	yes
--	-----

## Accessories

<b>ZEL 110</b>	196420
----------------	--------

<b>ABK 503/ 4 GW</b>	193814
----------------------	--------