



Screwless Connectors
Luminaire Connectors

LK 980-01 RZ/ 3 BD N PE L

terminal block, 3 pole, insulating material: PA, fixing: catch pin, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm²



Order Info

| | |
|----------------------------|---------------|
| reference number (ref.no.) | 21868 |
| PU | 500 |
| EAN | 4028012100286 |

Type

| | |
|-------------------------|---------------------|
| type | terminal block |
| number of poles | 3 pole |
| clamping units per pole | 2 |
| colour | white |
| cross-section rating | 2.5 mm ² |
| connection type | screwless |

Technical Data

| | |
|-------------------------------------|---------------------------|
| voltage rating | 450 V |
| current rating | 24 A |
| insulating material | PA |
| contact material | Spring Steel, Copper |
| flammability rating | V-2 |
| max. ambient temperature operation | 85 °C |
| stripping length | 8.0-9.0 mm |
| wall thickness min. | 0.5 mm |
| wall thickness max. | 1.2 mm |
| internal core cross-section min. | 0.5 mm ² |
| internal core cross-section max. | 1.5 / 2.5 mm ² |
| external core cross-section min. | 0.5 mm ² |
| external core cross-section max. | 2.5 mm ² |
| fixing | catch pin |
| type of conductor solid external | yes |
| type of conductor flexible external | yes |
| type of conductor solid internal | yes |
| type of conductor stranded internal | yes |
| ammonia resistance | yes |

Approvals

acc. to EN 60998

[Download PDF](#)

acc. to UL

[Download PDF](#)

Accessories

ZEL 110

196420

ZEL 900

196423
