



Screwless Connectors  
Luminaire Connectors

LK 980-01 RZ/ 3 SK

terminal block, 3 pole, insulating material: PA, fixing: catch pin, PE  
terminal: SK, voltage rating: 450 V, current rating: 24 A, cross-section  
rating: 2.5 mm<sup>2</sup>



Order Info

reference number (ref.no.)	21875
PU	500
EAN	4028012100590

Type

type	terminal block
number of poles	3 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>
connection type	screwless

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA
contact material	Spring Steel, Copper
flammability rating	V-2
max. ambient temperature operation	85 °C
stripping length	8.0-9.0 mm
wall thickness min.	0.5 mm
wall thickness max.	1.2 mm
internal core cross-section min.	0.5 mm <sup>2</sup>
internal core cross-section max.	1.5 / 2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
fixing	catch pin
type of conductor solid external	yes
type of conductor flexibel external	yes
type of conductor solid internal	yes
type of conductor stranded internal	yes

<b>PE terminal</b>	SK
<b>ammonia resistance</b>	yes

## Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>

## Accessories

<b>WKZ 980-01</b>	999041
<b>ZEL 110</b>	196420
<b>ZEL 900</b>	196423