



SMD Connectors

SMDflat 545/ 2 BRÜ

terminal block, pin spacing: 6.00 mm, 1 pole, current rating: 16.0 A, voltage rating: 250 V, connection type: screwless



Order Info

| | |
|------------------------------------|--------------------|
| reference number (ref. no.) | 22126 |
| PU | 376 (tape-on-reel) |
| EAN | 4028012121793 |

Type

| | |
|--------------------------------|----------------|
| type | terminal block |
| number of poles | 1 pole |
| clamping units per pole | 2 |
| colour | white |
| connection type | screwless |

Technical Data

| | |
|---|----------------------|
| voltage rating | 250 V |
| current rating | 16.0 A |
| insulating material | PPA-GF |
| contact material | Spring Steel, Copper |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 2.5 mm ² |
| impulse voltage rating | 2.5 kV |
| flammability rating | V-0 |
| max. Ambient Temperature Operation | 85 °C |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 9.0-10.0 mm |
| pin spacing | 6.00 mm |
| lower limit temperature | -40 °C |
| upper limit temperature | 150 °C |