



Circular Terminal Blocks IP68  
Circular Terminal Blocks AC 179 kompakt  
**AC 179 SK/ 4 SL L LWD**



### Order Info

|                             |       |
|-----------------------------|-------|
| reference number (ref. no.) | 26753 |
| PU                          | 200   |

### Type

|                 |  |
|-----------------|--|
| Type            | terminal block longitudinally watertight |
| connection type | screw                                    |
| number of poles | 4 pole                                   |
| colour          | green black                              |
| centre stop     | yes                                      |
| strain relief   | yes                                      |

### Electrical Data

|               |        |
|---------------|--------|
| rated voltage | 450 V  |
| rated current | 17.5 A |

### Connection Data

|                          |                                     |
|--------------------------|-------------------------------------|
| clamping range           | 0.5 - 4.0 mm <sup>2</sup>           |
| sheathing cable diameter | 7.0 - 13.0 mm                       |
| type of conductor        | fine stranded, stranded, solid      |
| stripping length         | 6.0 mm                              |
| dismantling length       | 25.0 mm                             |
| clamping units per pole  | 1                                   |
| grommet assembly         | 2.0 Nm                              |
| contact screw assembly   | M3 - max. $\curvearrowright$ 0.8 Nm |
| pole marking             | 1-2-3-4                             |
| strain relief assembly   | $\curvearrowright$ 2.5 Nm           |

### Ambient Conditions

|   |           |
|---|-----------|
| T <sub>max</sub> ambient air (at rated current) | 85 °C     |
| T <sub>max</sub> component (operation)          | 125 °C    |
| T <sub>min</sub> component (operation)          | -40 °C    |
| IP Code acc. to EN 60529                        | IP68/IP69 |

## Materials

|  |       |
|--|-------|
| <b>insulator material</b>                | PA    |
| <b>contact material</b>                  | brass |
| <b>flammability rating acc. to UL 94</b> | V-0   |

## Approvals

|                         |     |
|-------------------------|-----|
| <b>acc. to EN 60998</b> | yes |
|-------------------------|-----|

## Accessories

|                          |        |
|--------------------------|--------|
| <b>AC 179 RVK/ 4 M20</b> | 749564 |
| <b>AC 173 BC SW</b>      | 26280  |
| <b>DR 16 1x14,0</b>      | 729031 |
| <b>DR 16 1x4,0</b>       | 729033 |
| <b>DR 16 1x6,5</b>       | 729034 |
| <b>DR 16 2x4,0</b>       | 729035 |
| <b>DR 16 2x5,5</b>       | 729036 |
| <b>DR 16 3x4,0</b>       | 729037 |
| <b>DR 16 4x3,5</b>       | 729038 |
| <b>DR 16 5x3,5</b>       | 729009 |
| <b>DR 16 RH</b>          | 729011 |
| <b>DR 16 GS</b>          | 729032 |