



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 179 kompakt

AC 179 SVH 4/ 4 SL L



Order Info

| | |
|-----------------------------|-------|
| reference number (ref. no.) | 26761 |
| PU | 50 |

Type

| | |
|-----------------|-------------|
| Type | distributor |
| connection type | screw |
| number of poles | 4 pole |
| colour | black |
| centre stop | yes |
| strain relief | yes |

Electrical Data

| | |
|---------------|--------|
| rated voltage | 450 V |
| rated current | 17.5 A |

Connection Data

| | |
|--------------------------|-------------------------------------|
| clamping range | 0.5 - 1.5 mm ² |
| sheathing cable diameter | 7.0 - 13.5 mm |
| type of conductor | fine stranded, stranded, solid |
| stripping length | 6.0 mm |
| dismantling length | 25.0 mm |
| clamping units per pole | 1 |
| grommet assembly | 2.0 Nm |
| contact screw assembly | M3 - max. \curvearrowright 0.8 Nm |
| pole marking | 1-2-3-4 |
| strain relief assembly | \curvearrowright 2.5 Nm |

Ambient Conditions

| | |
|---|-----------|
| T _{max} ambient air (at rated current) | 85 °C |
| T _{max} component (operation) | 125 °C |
| T _{min} component (operation) | -40 °C |
| IP Code acc. to EN 60529 | IP68/IP69 |

Materials

| | |
|--|-------|
| insulator material | PA |
| contact material | brass |
| flammability rating acc. to UL 94 | V-0 |

Approvals

| | |
|-------------------------|-----|
| acc. to EN 60998 | yes |
|-------------------------|-----|

Accessories

| | |
|--------------------------|--------|
| AC 179 RVK/ 4 M20 | 749564 |
| AC 173 BC SW | 26280 |
| DR 16 1x14,0 | 729031 |
| DR 16 1x4,0 | 729033 |
| DR 16 1x6,5 | 729034 |
| DR 16 2x4,0 | 729035 |
| DR 16 2x5,5 | 729036 |
| DR 16 3x4,0 | 729037 |
| DR 16 4x3,5 | 729038 |
| DR 16 5x3,5 | 729009 |
| DR 16 RH | 729011 |
| DR 16 GS | 729032 |