



## SMD Connectors

### SMDflat 545/ 2

terminal block, pin spacing: 6.00 mm, 2 pole, current rating: 16.0 A, voltage rating: 400 V, connection type: screwless



## Order Info

<b>reference number (ref. no.)</b>	351402
<b>PU</b>	376 (tape-on-reel)
<b>EAN</b>	4028012121786

## Type

<b>type</b>	terminal block
<b>number of poles</b>	2 pole
<b>clamping units per pole</b>	1
<b>colour</b>	white
<b>connection type</b>	screwless

## Technical Data

<b>voltage rating</b>	400 V
<b>current rating</b>	16.0 A
<b>insulating material</b>	PPA-GF
<b>contact material</b>	Spring Steel, Copper
<b>core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>core cross-section max.</b>	2.5 mm <sup>2</sup>
<b>impulse voltage rating</b>	2.5 kV
<b>flammability rating</b>	V-0
<b>max. Ambient Temperature Operation</b>	85 °C
<b>type of conductor solid</b>	yes
<b>type of conductor flexible</b>	yes
<b>type of conductor stranded</b>	yes
<b>stripping length</b>	9.0-10.0 mm
<b>pin spacing</b>	6.00 mm
<b>lower limit temperature</b>	-40 °C
<b>upper limit temperature</b>	105 °C