



Circular Terminal Blocks IP68  
Circular Terminal Blocks AC 180 basic  
**AC 180 SK/ 5 SL terminal block**



terminal block, 5 pole, voltage rating: 450 V, current rating: 17.5 A, cross-section rating: 4.0 mm<sup>2</sup>

### Order Info

<b>reference number (ref. no.)</b>	741065SK
<b>PU</b>	200
<b>EAN</b>	4028012159581

### Type

<b>type</b>	terminal block
<b>number of poles</b>	5 pole
<b>clamping units per pole</b>	1
<b>colour</b>	black
<b>cross-section rating</b>	4.0 mm <sup>2</sup>

### Technical Data

<b>voltage rating</b>	450 V
<b>current rating</b>	17.5 A
<b>insulating material</b>	PA 6.6
<b>contact material</b>	brass
<b>flammability rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>IP code</b>	IP68
<b>type of conductor solid</b>	yes
<b>type of conductor flexible</b>	yes
<b>type of conductor stranded</b>	yes
<b>stripping length</b>	8.0 mm
<b>dismantling length</b>	30.0 mm
<b>Assembly Contact Screw</b>	0.5x3.0 / ⌀ 0.5 Nm
<b>lower limit temperature</b>	-40 °C
<b>upper limit temperature</b>	125 °C